


**WELL LOG AND REPORT TO THE STATE ENGINEER
OF NEVADA**

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57631
 Rec. 19.
 Well No.
 Permit No.
 Do not fill in.



Owner Hal J. Beesley Driller Effinger Drill & Pump Serv.
 Address 1400 Jessica Avenue Address Box 579 Lic. No. 212
 Location of well: SW 1/4 SW 1/4 Sec 34, T 20 N/S, R 62 E, in Clark County
 or S.E. Cor. Silver & Beesley

Water will be used for Domestic Total depth of well 100 feet
 Size of drilled hole 12 inch Weight of casing per linear foot
 Thickness of casing 10 Gauge Temp. of water
 Diameter and length of casing 8" ID 100 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Welded cap on top of casing.
 If nonflowing well give depth of standing water from surface 43 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well January 14, 1965 Date of completion of well January 15, 1965

Type of well rig "Walker-Neer 31"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sandy Clay
2	5	3	Caliche
5	26	21	Rock Sand & Gravel
26	28	2	Limestone
28	49	21	White Clay
49	56	7	Limestone & Gravel (Water)
56	69	13	Yellow Sandy Clay
69	75	6	Limestone (Water)
75	83	8	White Clay
83	86	3	Limestone (Water)
86	100	14	Yellow Clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 83 to 86 ft.

Other aquifers 69-75

First water at 49 feet.

Casing perforated
 from 60 to 95 ft.

Size of perforations
1/8 X 12" Torch

RECEIVED

JAN 18 1965

DEPT. OF WATER RESOURCES
 BRANCH OFFICE
 LAS VEGAS, NEVADA

