WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57909
Rec. 19
Well No. 884
Permit No. 14988
Do not fill in

No copy to ca.

Owner J. Fulcher Driller S. R. McKinney & Son

Address 300 Desert Inn Rd. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: ~~NE~~ SW ¼ ~~NW~~ SE ¼ Sec. ~~15~~ 9, T. 21N/S, R 61E, in Clark County

or

Water will be used for Domestic Total depth of well 190 ft.

Size of drilled hole 12" to 145, 8" to 190 Weight of casing per linear foot 28 lb.

Thickness of casing 5/16" Temp. of water

Diameter and length of casing 160 ft 8" I.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 ft. 9. 76 M.P. Bottom of 1½" and not in above surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well March 6, 1953 Date of completion of well March 12, 1953

Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Surface sand
3	11	7	gravel dry
11	18	7	caliche water
18	23	5	white clay
23	26	3	caliche water
26	30	4	white clay
30	33	3	caliche water
33	49	16	white clay
49	53	4	caliche water
53	75	22	white clay
75	76	1	gyp rock water
76	125	49	brown sandy clay
125	128	3	cement gravel water
128	142	14	red sandy clay
142	144	2	cemented gravel
144	162	18	red sandy clay
162	164	2	gyp rock
164	184	20	red sandy clay ~~water~~
184	186	2	gyp rock water
186	190	4	red sandy clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 184 to 186 ft.

Other aquifers 125 to 128
75 to 76

First water at 11 feet.

Casing perforated

from 60 to 160 ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" I.D.	0	160	160	8" cemented down to 50 ft with ~~xxx~~ 3 yd. concrete Hole gravel packed from 50 ft to 145 ft

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

bailed 40 G.P.M. lowered water level to 85 ft.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature]
Well Driller

By.....

License No. 45

Dated 3-21, 1953

(Not to be filled in by Driller)