

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57960
 Rec. _____
 Well No. _____
 Permit No. _____
Do not fill in

I

Owner Fred Stoye Driller S. R. McKinney & Son
 Address 1006 Sangert St. Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45
 Location of well: SE 1/4 SW 1/4 Sec. 5, T. 22N/S, R. 61E, in Clark County
 or West 1/2 of SW 1/4 of SE 1/4 of SW 1/4 of Section 5, Twp 22, Range 61 East.
 Water will be used for Domestic Total depth of well 180 ft.
 Size of drilled hole 13" to 55 ft., 10" to 161. Weight of casing per linear foot 10 guage
 Thickness of casing 10 guage 8" to 180 Temp. of water _____
 Diameter and length of casing 6" I.D. to 160 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 129 ft.
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well Aug 28, 1955 Date of completion of well Sept 1, 1955
 Type of well rig 72 Speed Star Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	sandy soil
6	8	2	gravel and sand
8	32	24	grey sandy clay
32	60	28	brown sandy clay
60	74	14	gravelly clay
74	94	20	hard gravelly clay
94	107	13	sandy clay
107	120	13	hard gravelly clay
120	129	9	soft sandy clay
129	131	2	gravelly clay
131	142	11	sandy clay
142	154	12	sand water
154	155	1	gravelly clay water
155	171	16	soft sandy clay
171	175	4	gravel and clay water
175	178	3	soft sandy clay
178	180	2	gravel and sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 178 to 180 ft.
171 to 175
 Other aquifers 154 to 155, 142 to 154

First water at 142 feet.

Casing perforated
 from 140 to 180 ft.

Size of perforations
3/16" x 10"

