

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57971
 Rec.
 Well No.
 Permit No.

Do not fill in



Owner Lester E. Carlisle Driller Nevada Pump & Supply Company
 Address Indian Springs, Nevada Address Las Vegas, Nevada Lic. No. 133
 Location of well: NW 1/4 SE 1/4 Sec. 6, T 22 N/S, R 61 E, in Clark County
 or
 Water will be used for Domestic Total depth of well 195 feet
 Size of drilled hole 12" Weight of casing per linear foot 12 lbs.
 Thickness of casing 10 gauge Temp. of water
 Diameter and length of casing 8" x 195'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 155 feet
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well June 2, 1955 Date of completion of well June 6, 1955
 Type of well rig Cable Tools

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|-------------------------|
| 0 | 30 | 30 | Boulders & Gravel |
| 30 | 40 | 10 | Caliche |
| 40 | 75 | 35 | Yellow Clay & Gravel |
| 75 | 80 | 5 | Caliche |
| 80 | 170 | 90 | Red Clay & Gravel-Water |
| 170 | 191 | 21 | Sand-Gravel-Water |
| 191 | 195 | 4 | Hard red Clay |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 170 to 191 ft.

Other aquifers 80 - 170

First water at 145 feet.

Casing perforated
 from 145 to 195 ft.

Size of perforations
1/16" x 6"



