

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 51983
 Rec. _____ 19____
 Well No. _____
 Permit No. _____



Do not fill in

Owner Leslie W. Davis Driller Nevada Pump & Supply Company

Address Box 527-A, Sandy, Utah Address Las Vegas, Nevada Lic. No. _____

Location of well: SE 1/4 SE 1/4 Sec. 6, T. 22 N/S, R. 61 E, in Clark County
 or _____

Water will be used for Domestic Total depth of well 201 feet

Size of drilled hole 10" Weight of casing per linear foot 9 lbs.

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 6" x 201'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 147 feet

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well May 30, 1955 Date of completion of well June 1, 1955

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top Soil
3	16	13	Caliche
16	157	141	Brown Sandstone
157	165	7	Sand-Gravel-Water Bearing
165	181	16	Sandstone
181	185	4	Coarse Gravel-Water Bearing
185	189	4	Sticky Clay
189	196	7	Sand-Gravel-Water Bearing
196	201	5	Sticky Red Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 189 to 196 ft.

Other aquifers 157-165

181-185

First water at 160 feet.

Casing perforated

from 156 to 201 ft.

Size of perforations

1/16" x 6"



