

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57988  
 Rec. .... 19  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Ann J Ford Driller John H Barnett  
 Address PO Box 2412 (Huntridge sta) L.V. Address 3401 E Van Buren L.V. Lic. No. 185  
 Location of well: ..... $\frac{1}{4}$ ..... $\frac{1}{4}$  Sec....., T.....N/S, R.....E, in..... Clark County  
 or. E $\frac{1}{2}$  SE $\frac{1}{4}$  SW $\frac{1}{4}$  SE $\frac{1}{4}$  Section 6, Township 22 south, Range 61 east.  
 Water will be used for..... Domestic ..... Total depth of well..... 180 feet  
 Size of drilled hole..... 10" to 50 feet 8" to 180 Ft Weight of casing per linear foot..... 8.60  
 Thickness of casing..... 1/4" 10 gauge Temp. of water.....  
 Diameter and length of casing..... 6" 180 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....  
 If nonflowing well give depth of standing water from surface..... 155 feet  
 If flowing well describe control works.....  
 (Type and size of valve, etc.)  
 Date of commencement of well..... December 22, 1954 Date of completion of well..... January 13, 1955  
 Type of well rig..... Ft Worth Spudder Model L

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	4	4	Sand and Gravel	
4	50	46	Hard rock	
50	55	5	Gravel dry	Chief aquifer (water-bearing formation) from <u>163</u> to <u>180</u> ft.
55	68	13	Hard rock	Other aquifers.....
68	73	5	Gravel dry	
73	112	39	Hard rock	
112	117	5	Shale and gravel	
117	137	20	Hard rock	First water at..... <u>163</u> feet.
137	163	26	Sandy shale and gravel	Casing perforated from <u>150</u> to <u>180</u> ft.
163	169	6	Sand and gravel (some water)	
169	180	11	Gravel (increase in water)	Size of perforations <u>1/4 inch</u>

