

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57999  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

*Coy R. Church*

Owner JOHN A. JENNINGS Driller Charlie Cribbs

Address Calamazoo Mich. Address 3200 Palomino lane Lic. No. 70

Location of well: 1/4 Sec. 1/4, T. N/S, R. E, in Clark County

or E 1/2 NE 1/4 SE 1/4 NE 1/4 Sec. 6 22S R 61 E

Water will be used for Domestic Total depth of well 180 ft.

Size of drilled hole 10 in Weight of casing per linear foot 12

Thickness of casing 10 Gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8 5/8 24 ft L  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 125

If flowing well describe control works Bailer tested 15 G.P.M. at 140 ft D D.  
 (Type and size of valve, etc.)

Date of commencement of well Feb. 15 / 55 Date of completion of well Feb. 21 / 55

Type of well rig Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
000	3	3	sand and gravel
3	8	5	brown sandy clay
8	48	40	brown sand stone
48	60	12	cement gravel
60	130	70	Brown sandy clay
130	135	5	bolders gravel (water)
135	165	30	brown sandy clay
165	170	5	gravel & sand (WATER)
170	180	10	red clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 165 to 170 ft.

Other aquifers 130

---

First water at 130 feet.

Casing perforated

from 130 to 180 ft.

1/8 X 1/4 in.

Size of perforations

