Log No. 58493
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Mr. Mofford ?

Owner: JOHN D COE Driller: J.E. METZ

Address: 2104 ASH LAS VEGAS Address: Mt Lynn Vegas Lic. No. 35

Location of well: S½ NE¼ NE¼ Sec. 5, T. 21 N/S, R. 62 E, in Clark County

or LOT 18 BLOCK 79 VEGAS MANOR #2.

Water will be used for: Domestic Total depth of well: 75'

Size of drilled hole: 8" bit Weight of casing per linear foot: 16#

Thickness of casing: 3/16 Temp. of water: 68

Diameter and length of casing: 1" [illegible] x 71' 3"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 18'

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: July 24 – 52 Date of completion of well: July 30 – 1952

Type of well rig .....

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	silt
6	19	13	gravel in clay
19	20	1	gravel (water – 18'
20	38	18	soft lime
38	50	12	gallichie
50	58	8	hard lime
58	69	11	broken lime (water
69	73	4	soft lime
73	75	2	hard lime

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 58 to 69 ft.

Other aquifers .....

First water at 20 feet.

Casing perforated
from 50 to 75 ft.

Size of perforations
3/16 x 6"
every 2 feet

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6" ID	1' 3" above	75'	76' 3"	Pea gravel Pack 45' - 75' Bal cemmented

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

bales 15 GPM down to 23'

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Joseph E Metz
Well Driller

By JEM

License No. 35

Dated Aug 1, 1952

(Not to be filled in by Driller)