

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No.	59132
Rec.	19
Well No.	
Permit No.	

Do not fill in

Owner Everett Krause Driller Douglas Slagle

Address Whitney, Nevada Address P.O. Box 2081 Lic. No. 137

Location of well: N~~1~~¹/₄ Sw¹/₄ Sec. 27, T.21N/S, R.62E, in Clark County

or In Whitney 50 Ft. OF the Hiway

Water will be used for Domestic Watering Total depth of well 80 Ft.

Size of drilled hole 8 In. Weight of casing per linear foot 9.1 lbs.

Thickness of casing 12 Gage Temp. of water Cold

Diameter and length of casing 8 3/8 I.D. 47 Ft. used in Well
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure --

If nonflowing well give depth of standing water from surface 9 Feet

If flowing well describe control works --
(Type and size of valve, etc.)

Date of commencement of well Dec. 8, 1953 Date of completion of well Dec. 10, 1953

Type of well rig Keystone 53 (50)

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	Lt. Brn. Silt, an White Clay
35	36	1	White Rock (Solid)
36	45	9	Rolling Gravel, Sand an Water
45	54	9	White Clay an Gravel
54	61	7	White Clay
61	63	2	Solid White Rock
63	74	11	Series of Clay, Sand, Sheet Rock, Gravel an Water
74	80	6	White Clay an Pebbles

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 36 to 45 ft.

Other aquifers 63 to 74 Ft.

First water at 36 to 45 feet.

Casing perforated
from 36 to 46 ft.

Size of perforations
3/16 x 1 In.

