WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 59240
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: John R Dykstra Driller: O.M. Gulbard
Address: 537 No. 11th St - Las Vegas - Nev Address: Box 452 Henderson - Nev Lic. No. 115
Location of well: NE 1/4 NW 1/4 Sec. 29, T. 21 N/S, R 62 E, in Clark County
or Plot #25 - Philmore Tract - Off Boulder Road
Water will be used for: Domestic Use Total depth of well: 102 feet
Size of drilled hole: 6" Weight of casing per linear foot: 10 Lbs.
Thickness of casing: 1/8" Temp. of water: .....
Diameter and length of casing: 6" OD 62' Long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure: 1/2 Gal. per Minute
If nonflowing well give depth of standing water from surface: .....
If flowing well describe control works: None at Present
(Type and size of valve, etc.)
Date of commencement of well: July 7-52 Date of completion of well: July 20-52
Type of well rig: Fort Worth Spudder Model - L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Sandy Yellow Clay
10	18	8	Red Clay
18	20	2	Limestone - 1st Water
20	60	40	Red Clay
60	75	15	Yellow Clay
75	78	3	Sandstone
78	90	12	Clay + Rock
90	95	5	Gravel - Fine Sand
95	102	7	Red Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 18 to 20 ft.
Other aquifers 90-95'

First water at 18 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6'	0	62'	62'	Cemented-In - 0-60 ft.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By.....

License No. 115

Dated August 9, 1952

(Not to be filled in by Driller)