

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 59288  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in

Owner Philip Freiburg Driller McGarvie Plumbing & Welding

Address 4584 Madre Meas Drive, Las Vegas, Nevada Address 221 N. 3rd St. Las Vegas, Nevada No 132

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec 29, T. 21 N/S, R. 2E, in Clark County

or Lot 54, Philmar Acres, Sec 29, T. 21 S, R. 2E

Water will be used for Domestic Total depth of well 100'

Size of drilled hole 6" Weight of casing per linear foot 4.9

Thickness of casing 14 ga. Temp. of water \_\_\_\_\_

Diameter and length of casing 72'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure This well flows about 2 gallons per hour

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works none  
(Type and size of valve, etc.)

Date of commencement of well November 18, 1953 Date of completion of well November 25, 1953

Type of well rig Keystone

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	sandy soil
8	43	51	sandy clay
51	3	54	gravel (water)
54	<del>12</del> 21	75	sandy clay
75	12	87	clay (imbedded gravel)
87	7	94	tough clay
94	3	97	sandy clay
97	3	100	tough blue clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 51 to 54 ft.

Other aquifers \_\_\_\_\_  
usable to full if  
water added water  
was encountered

First water at 51 feet.

Casing perforated

from None to \_\_\_\_\_ ft.

Size of perforations

None



