

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **59378**
 Rec. _____
 Well No. _____
 Permit No. _____

Do not fill in

Owner C. H. Koegel Driller S. R. McKinney & Son

Address 1124 West 10th St. San Pedro, Calif. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SE 1/4 NW 1/4 Sec. 16, T. 22 N/S, R. 61 E, in Clark County
 or SE 1/4 of NW 1/4 of SE 1/4 of NW 1/4 of Section 16, Twp. 22, Range 61 East

Water will be used for Domestic Total depth of well 150 ft.

Size of drilled hole 12" to 52 ft, 10" to 150 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water _____

Diameter and length of casing 8" I.D. to 150 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 87 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Nov. 21, 1955 Date of completion of well Nov. 25, 1955

Type of well rig Bugyrus Erie 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material.
0	2	2	soil and clay
2	25	23	cement gravel
25	75	50	sandy clay
75	90	15	sand and clay
90	115	25	sandy clay
115	125	10	sand and gravel water
125	134	9	red sandy clay
134	142	8	gravel water
142	150	8	red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 134 to 142 ft.

Other aquifers 115 to 125

First water at 115 feet.

Casing perforated

from 110 to 150 ft.

Size of perforations

3/16" X 10"

