

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 59561
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner Silver State Savings & Loan Co. *Kennedy?* Driller John H Barnett
 Address 431 Fremont St. Las Vegas, Nevada Address 3401 East Van Buren Lic. No. 185
 Location of well: $\frac{1}{4}$ Sec. 16, T22 N/S, R 61 E, in Clark County
 or S-1/2 SW-1/4 SW-1/4 NW-1/4
 Water will be used for Domestic Total depth of well 170
 Size of drilled hole 8-5/8 Weight of casing per linear foot 8.60
 Thickness of casing 10 gauge Temp. of water _____
 Diameter and length of casing 6" - 140 feet (Liner 40 feet 8-5/8 casing cemented in)
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 95 feet before deepening 88 feet after.
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well November 10, 1956 Date of completion of well November 18, 1956
 Type of well rig Fort Worth Spudder Model L

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|---|---------|----------------|------------------|
| 125 | 158 | 33 | Cement rock |
| 158 | 170 | 12 | Sand rock |
| DRILLING DEEPER AND SETTING 140 FEET 6" LINER | | | |



Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 158 to 170 ft.

Other aquifers _____

First water at 158 feet.

Casing perforated
 from 90 to 170 ft.

Size of perforations
1/8"



