


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 59654
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in



Owner Anthony Fiero & Albert Marchine Driller Douglas Slagle

Address 1098 Sir Patrick Address 4518 E. Vegas Vally Dr. Lic. No. 137

Location of well: S. W 1/4 N. W 1/4 Sec 31., T21 N, R62 E, in Clark County
 or 4th. Lot E. of Pecos on N. side of Patrick St.

Water will be used for Domestic Total depth of well 125ft.

Size of drilled hole 12" for 8" casing Weight of casing per linear foot 12.15 lb.

Thickness of casing 10 gage Temp. of water cool

Diameter and length of casing 8" X 125 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. ---

If nonflowing well give depth of standing water from surface 18 Inches

If flowing well describe control works. ---
 (Type and size of valve, etc.)

Date of commencement of well April 29, 1967 Date of completion of well May 3, 1967

Type of well rig Bucyrus-Erie 22W Series 2

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Fill
1	17	16	Soft caleche & white clay
17	19	2	Red clay
19	20	1	Soft rock
*20	22	2	Gravel & Water
22	34	12	White clay
34	40	6	Light brown clay
40	47	7	White clay
47	52	5	Sandy red clay
52	58	6	Silky red clay
*58	73	15	Soft sandy red clay and Water
73	78	5	Hard rock
78	83	5	Light brown clay
*83	101	18	Series of red clay and Water
101	125	14	Red clay and pea Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 83 ft. to 101 ft.

Other aquifers 20 ft. to 22 ft.
58 ft. to 73 ft.

First water at 20 feet.

Casing perforated
 from 50 ft. to 125 ft.

Size of perforations
1/8 X 12"

JUNE 11 1967
 DIV. OF WATER RESOURCES
 LAS VEGAS, NEVADA

