WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 59816
Permit No.
Basin 212

NOTICE OF INTENT NO. 8397

1. OWNER John Ogden
MAILING ADDRESS 8620 N Maverick
Lv NV 89131

ADDRESS AT WELL LOCATION Same
8620 mustang

2. LOCATION SW ¼ NW ¼ Sec. 11 T. 19 N/S R. 60 E/W Clark County
PERMIT NO. (Issued by Water Resources) | 480-350-026 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay & Gravel		0	50	
Clay Sand Gravel		50	65	
Sand & Gravel		65	80	
Sand & Gravel Boulder		80	110	
Cemented Sand Gravel		110	155	
Cemented Sand Gravel	10-15	155	200	
Brown Clay		200	245	
Cemented Sand Gravel	15-20	245	275	
Clay		275	290	
Cemented Sand Gravel		290	340	
Brown Clay's		340	360	
Cemented Sand Gravel		360	380	
Same + Boulders	50-60	380	405	

DCNR/DWR Received APR 10 1996 LAS VEGAS OFFICE

Date started 3-16, 1996
Date completed 3-28, 1996

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50-60		

8. WELL CONSTRUCTION
Depth Drilled 405 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12¼ Inches		0 Feet	4 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	17 LB	188	0	400

Perforations:
Type perforation Torch
Size perforation 1/8
From 360 feet to 400 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☑ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 55 feet to 400 feet

9. WATER LEVEL
Static water level 140 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Redd'n Drilling (Contractor)
Address 8170 S Hacienda (Contractor)
Lv NV 89123
Nevada contractor's license number issued by the State Contractor's Board 38255
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1798
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 3-28-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627