

Sx

NE CARD

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 60412  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

### Deepening Job

Owner Clas Lamb Driller S.R. McKinney & Sons

Address 5507 North Drexel, L.V. Address 1042 So. Main Lic. No. 45

Location of well: N 1/4 NE 1/4 Sec 34, T19 N/S, R60 E, in Clark County

Water will be used for Domestic use Total depth of well 230

Size of drilled hole 12" to 50' & 10" to 230' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" ID to 230'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 105 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 4/5/63 Date of completion of well 4/19/63

Type of well rig Eucyrus Erie 221

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
100	150	50	clay & gravel streaks
150	195	45	clay & gravel streaks
195	230	35	gravel & clay streaks

*Deepened one of Lloyd Jones' wells.*

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 105 to 150 ft.

Other aquifers 150 to 195 ft.

195 to 230 ft.

First water at 105 feet.

Casing perforated

from 105 to 230 ft.

Size of perforations

3/16" x 10"



