

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **60686**  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Mrs. Jewell Bailey Driller S.R. McKinney & Son

Address 604 West Bonanza, Las Vegas, Nev. Address 1042 South Main. L.V. Lic. No. 45

Location of well: SE 1/4 SE 1/4 Sec 34, T19 N/S, R61 E, in Clark County

Water will be used for Domestic Total depth of well 125'

Size of drilled hole 12" to 50, 10" to 125' Weight of casing per linear foot 10 Guage

Thickness of casing 10 Guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 125'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well May 19, 1955 Date of completion of well May 20, 1955

Type of well rig 72 Speed Star, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	34	34	Brown Clay
34	48	14	White Clay
48	50	2	White sand water
50	67	17	Brown Clay
67	70	3	Brown Sand water
70	76	6	Brown Clay
76	79	3	Sand stone water
79	88	9	Brown Clay
88	90	2	Brown sand water
90	97	7	Brown Clay
97	100	3	Brown Sand water
100	111	11	Brown Clay
111	114	3	Brown sand water
114	125	11	Brown Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 111 to 114 ft.

Other aquifers 97' to 100'  
88' to 90'

76' to 79'  
67' to 70'  
48' to 50'

First water, at 48 feet.

Casing perforated  
 from 85 to 125 ft.

Size of perforations  
3/16 x 10"

V

