


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 60710  
 Rec. ....  
 Well No. ....  
 Permit No. ....



*Do not fill in*

Owner Ernest R. Watts Driller Louis F. Evans

Address Box 340 North Las Vegas, Nevada Address 2020 Carroll N. Las Vegas Loc. No. 117

Location of well: S. E. 1/4 NW 1/4 Sec. 34, T. 19N/S, R. 61 E, in Clark County

Water will be used for Domestic Total depth of well 100 Ft.

Size of drilled hole 100 ft. 10 inch. Weight of casing per linear foot 6" o.d. 9.28 6 5/8 od  
17.16

Thickness of casing 6" O.D. 10 ga. 6-5/8 1/4 wall Temp. of water .....

Diameter and length of casing 6" O.D. 45 ft. 6-5/8 O.D. 55 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 53 ft.

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well May 6, 1957 Date of completion of well May 13, 1957

Type of well rig Armstrong

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	sand
1	42	41	gyp
41	55	13	gray clay
55	72	17	gray clay & gravel (water)
72	87	15	gray clay
87	100	13	gray clay & gravel (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 87 to 100 ft.

Other aquifers 55 to 72

First water at 55 feet.

• Casing perforated

from 60 to 100 ft.

Size of perforations

1/4 inch wide 6 inches long



