


5x

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 6071
 Rec. _____
 Well No. _____
 Permit No. _____
Do not fill in



Owner Herbert R. Williams Driller S. R. McKinney & Sons, Inc.

Address United Title Ins., L.V. Address 1042 So. Main Lic. No. 45

Location of well: NE 1/4 SE 1/4 Sec. 34, T. 19 N/S, R. 61 E, in Clark County
or _____

Water will be used for Domestic Total depth of well 125'

Size of drilled hole 12" to 50', 10" to 125' Weight of casing per linear foot .188

Thickness of casing .188 Temp. of water _____

Diameter and length of casing 8" ID from 0' to 125'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 47'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 7/31/62 Date of completion of well 8/3/62

Type of well rig Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Caliche
6	23	17	brown clay & gravel
23	42	19	white clay
42	44	2	gravel
44	50	6	grey clay
50	80	30	sandy clay
80	82	2	gravel (water)
82	90	8	clay
90	92	2	gravel (water)
92	100	8	sandy clay
100	102	2	gravel
102	115	13	white clay
115	118	3	gravel (water)
118	125	7	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 115 to 118 ft.

Other aquifers 80 to 82'
90 to 92'

First water at 80 feet.

Casing perforated
 from 55 to 125 ft.

Size of perforations
3/16" x 10"



