X

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 62569
Rec. ..... 19..
Well No. .....
Permit No. .....
Do not fill in

Owner: IHman -R.T. Inman Driller: Rodgers & Cribbs

Address: Goodsprings Address: 2710 Palomino Lane 156 Lic. No. .....

Location of well: ..... ¼ ..... ¼ Sec. 26, T. 24 N/S, R. 58 E, in clark County

or at the west edge of goodsprings

Water will be used for: domestic Total depth of well: 80

Size of drilled hole: 10 Weight of casing per linear foot: .....

Thickness of casing: 8 in O.D. Temp. of water: .....

Diameter and length of casing: 8 in O D .
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 30

If flowing well describe control works: .....
(Type and size of valve, etc.)

Date of commencement of well: june 10 Date of completion of well: june 14

Type of well rig: spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
000	4	4	sand and gravel
4	14	10	coliechie
14	24	10	white clay
24	45	21	lime rock
45	50	5	broken lime rock WATER
50	70	20	white lime hard
70	75	5	broken rock WATER
75	80	5	lime Hard

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 45 to 50 ft.

Other aquifers: 75

First water at ..... feet.

Casing perforated
from 45 to 70 ft.

Size of perforations: .....

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
				8 in O.D. casing perforated 45 to 80 cemented 45 to surface

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By S.E. Rodgers

License No. 106

Dated June 15, 1960

(Not to be filled in by Driller)