WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

HDDW-2
STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 25569 64195
Permit No.
Basin 001

NOTICE OF INTENT NO. 25569

1. OWNER NEWMONT GOLD COMPANY
MAILING ADDRESS P.O. BOX 669
CARLIN, NEVADA 89822

ADDRESS AT WELL LOCATION
NEWMONT GOLD MINE

2. LOCATION NE ¼ NE ¼ Sec. 10 T. 35 N/S R. 50 E. Eureka County
PERMIT NO. 61859-T (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
VININI FORMATIONS/				
QUARTZ HORNFELS		0	1420	1420
RODEO CREEK/				
QUARTZ HORNFELS		1420	1700	280
PAPOWICH/CALESILIATE				
HORNFELS		1700	2020	320
ROBERTS MTNS/SILTY				
LIMESTONE		2020	2220	200

Date started 5-14, 1996
Date completed 6-15, 1996

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
740		1

8. WELL CONSTRUCTION
Depth Drilled 2220 Feet Depth Cased 2210 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
46" Inches		0' Feet	40' Feet
31" Inches		40' Feet	1400' Feet
22" Inches		1400 Feet	2220 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
40"	156	3/8"	0	40
24"	95	3/8"	0	1400'
16"	63	3/8"	+2	1537
16"	63	3/8"	2139	2210

Perforations:
Type perforation LOUVERED
Size perforation
From 1537 feet to 2139 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-40+0-1400+0-100
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 2220 feet to 100 feet

9. WATER LEVEL
Static water level 870 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature cool °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 W 1500 South (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1939

Signed KEVIN ELLISON Kevin Ellison
By driller performing actual drilling on site or contractor

Date 06-16-96

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627