WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64985
Permit No.
Basin 059

NOTICE OF INTENT NO. [redacted]34004

1. OWNER Battle Mt. Gold
MAILING ADDRESS Copper Canyon Mine Complex Battle Mt Nevada
ADDRESS AT WELL LOCATION East Philadelphia Canyon

2. LOCATION NW ¼ SW ¼ Sec 26 T 31 N (N)/S R 43 E Lander County
PERMIT NO. M/D-967-H (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [X] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Broken Rock & Clay & Gravel		0	5	5
Rock		5	280	275
Broken Rock & with water		280	335	
Broken Rock & with Void in Rock		335	352	
Hard Rock from		352	480	
Cemented Back To 375' filled Void in with 1/8 & 1/4 Washed Gravel And Cement with Bentonite pellets from 334' to [redacted] 346'. Cement from 333' To 346'				

Date started 10-6, 19 96
Date completed 11-3, 19 96

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1½	300'	14 ½ hr.

8. WELL CONSTRUCTION
Depth Drilled 480 Feet Depth Cased 480 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
11 7/8 Inches		0 Feet	12 Feet
8 Inches		12 Feet	176 Feet
6 Inches		176 Feet	480 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8		.250'	+1.42	7
6	[redacted]	.188 wall	+1.42	176'
2"		pvc	+1.42	[redacted]333'

Perforations:
Type perforation .02 slotted screen pvc
Size perforation .02 slot screen
From 300 feet to 333 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 204'
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 280 feet to 333 feet

9. WATER LEVEL
Static water level 234 feet below land surface
Artesian flow 1½ - 2 G.P.M. [redacted] P.S.I.
Water temperature 48 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name O'Keefe Drilling (Contractor)
Address Box 3810 Butte Mt. 58702 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board C-23-00-30581
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1703
Signed Frank Camp (By driller performing actual drilling on site or contractor)
Date 11-17-96

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627