WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65884
Permit No.
Basin 080

NOTICE OF INTENT NO. 35830

1. OWNER Gary & Terri Tompkins
MAILING ADDRESS 9200 S. Beechcraft
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
TNT Farms-9200 S. Beechcraft Winnemucca NV 89445

2. LOCATION NE 1/4 SW 1/4 Sec. 26 T 35N N/S R 37 E Humboldt County
PERMIT NO. 13970 (Issued by Water Resources) | Parcel No. | Well #5 (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Surface Clay		0	40	40
Sandy Clay		40	220	180
Sand & Gravel		220	230	10
Sandy Clay		230	330	100
White Clay		330	335	5
Hard White Shale		335	338	3
Sandy Clay		338	514	176

Date started 12/16/96, 19__
Date completed 12/20/96, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☒ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1500	150	18

8. WELL CONSTRUCTION
Depth Drilled 514 Feet Depth Cased 500 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
26	Inches	0	Feet	514	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	+1	140

Perforations:
Type perforation Single Row Mill SLot
Size perforation 1/4 X 3 & 1/8 X 3
From 140 16" feet to 320 1/4x3 MS feet
From 320 12" feet to 500 1/8 X 3 MS feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 500 feet

9. WATER LEVEL
Static water level 55 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 West Winnemucca Blvd. (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed [signature]
By driller performing actual drilling on-site or contractor

Date 1-17-97