

OFFICE USE ONLY
 Log No. 65956
 Permit No. 961
 Basin 961
 NOTICE OF INTENT NO. 36031

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER BARRICK GOLDSTRIKE ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE
 MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

2. LOCATION NW 1/4 NE 1/4 Sec 19 T 36 N 50 E EUREKA County
 PERMIT NO. 55146 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE VERTICAL DRAIN
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BROWN ROCK & BROWN CLAY		0	130	130
BROWN CLAY		130	155	25
TAN ROCK & BRONW CLAY		155	190	35
BROWN CLAY, GRAY ROCK		190		
MOTTLEY ROCK			250	60
BROWN CLAY		250	355	105
OXIDIZED BRONW, BLACK ROCK		355	455	100
BROWN & BLACK ROCK &		455		
BROWN CLAY			500	45
BROWN CLAY		500	520	20
BLACK, BROWN ROCK &		520		
BROWN CLAY			540	20
BRONW CLAY/ROCK		540	640	100
CLAY		640	650	10
DARK BROWN/BLACK ROCK		650	690	40
TAN CLAY/ROCK		690	710	20
FRACTURED BROWN ROCK		710	800	90

8. WELL CONSTRUCTION
 Depth Drilled 810 Feet Depth Cased 800 Feet

HOLE DIAMETER (BIT SIZE)
 From To
17-1/2 Inches 0 Feet 37 Feet
9-7/8 Inches 37 Feet Feet
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12	33.38	.250	0	37
6	17.02	.250	0	120

Perforations:
 Type perforation LOUVERED
 Size perforation .125
 From 800 feet to 120 feet
 From feet to feet
 From feet to feet
 From feet to feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 37 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 810 feet to 50 feet

9. WATER LEVEL
 Static water level 189.6 feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature 63 °F Quality

Date started MARCH 10 19 97
 Date completed MARCH 16 19 97

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
43	551.2	1 HR

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING Contractor
 Address 2286 WEST 1500 SOUTH Contractor
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number 0021976
 issued by the State Contractor's Board.

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1939

Signed KEVIN ELLISON *Kevin E. Ellison*
 By driller performing actual drilling on site or contractor

Date MARCH 17, 1997