



PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36058

1. OWNER Silver State Ranches ADDRESS AT WELL LOCATION North End Newark Valley, Near Cold Creek Ranch
 MAILING ADDRESS P.O. Box 611
Eureka, Nevada 89316
 2. LOCATION SW 1/4 NW 1/4 Sec. 24 T. 23 N 55 E White Pine County
 PERMIT NO. None - Undesignated 07-250-02
 Basin - permit applied for _____ Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
White Clay		0	5	5
White Clay-fine gravel		5	10	5
Clay, fine gravel-sand		10	20	10
Red Clay, Rounded Gravel		20	35	15
Clean Well Rounded Gravel		35	40	5
Yellow Clay, Stringers Gr.		40	55	15
Clean-Well Rounded Grav.		55	85	30
Yellow Clay - Stiff		85	90	5
Broken Gravel, Clay String.		90	100	10
Gray Clay and Gravel		100	115	15
Sand and Fine Gravel		115	120	5
Fine Broken Gravel		120	130	10
Sand & Gravel Mixed		130	140	10
Sand w Red Clay		140	158	18
Gravel		158	165	7
Clay and Gravel		165	190	25
Red Clay		190	205	15
Cemented Sand		205	215	10
Red Clay w Gravel		215	225	10
Sandstone w Gravel		225	235	10
Red Clay		235	245	10
Sandstone w Gravel		245	255	10
Clay and Gravel		255	265	10
Sandstone w Gravel		265	270	5
Clay and Gravel, Sandstone		270	310	40
Clay Gravel Mixed		310	317	7
Clay Sandstone, Gravel		317	330	13
Clay Gravel Mixed		330	340	10
Red Clay Gravel Mixed		340	380	40
Red Clay Minor Gravel		380	460	80

Date started 6/4/97 to 6/26/97, 1997
 Date completed 6/4/97 to 6/26/97, 1997

8. WELL CONSTRUCTION
 Depth Drilled 460 Feet Depth Cased _____ Feet
 HOLE DIAMETER (BIT SIZE)
 From To
8 1/2 Inches 0 Feet 460 Feet
28 Inches 0 Feet 400 Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42.05	.250	+1	111

Perforations:
 Type perforation Perf 1/8 triple slot, factory
 Size perforation 100 slot Johnson Screen
 From Perf 110 feet to 220 feet
 From Screen 220 feet to 260 feet
 From Perf 260 feet to 330 feet
 From Screen 330 feet to 350 feet
 From Perf 350 feet to 400 feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 50 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 400 feet

9. WATER LEVEL
 Static water level 12.5 feet below land surface
 Artesian flow --- G.P.M. _____ P.S.I.
 Water temperature Cool °F Quality Good

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
800	181.7	11

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Sargent Irrigation Company Contractor
 Address 9955 North Virginia Street Contractor
Reno, Nevada 89506
 Nevada contractor's license number issued by the State Contractor's Board 0021246
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1413-T
 Signed [Signature] Driller performing actual drilling on site or contractor
 Date June 27, 1997