WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

INT OR TYPE ONLY
NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68809
Permit No.
Basin 071

NOTICE OF INTENT NO. 36182

1. OWNER Gary & Terri Tompkins
MAILING ADDRESS 9200 S. Beechcraft
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
Rose Street
Winnemucca, NV 89445

2. LOCATION NE 1/4 NE 1/4 Sec. 31 T 35N N/S R 38 E Humboldt County
PERMIT NO. (Issued by Water Resources) 10-451-46 (Parcel No.) Rawhide Estates (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay		0	2	2
Cobbles		2	125	123
Clay		125	200	75
Cobbles		200	241	41
Clay		241	259	18
Cobbles		259	286	27
Clay		286	320	34
Fractured Basalt		320	364	44

Date started 5/3/97, 19__
Date completed 5/5/97, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30		3 hrs.

8. WELL CONSTRUCTION
Depth Drilled 364 Feet Depth Cased 360 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 7/8	Inches	0	Feet	364	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	360

Perforations:
Type perforation Single row mill slot
Size perforation 1/8 X 3
From 260 feet to 360 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 100 feet to 364 feet

9. WATER LEVEL
Static water level 240 feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2019

Signed Terri Tomp (By driller performing actual drilling on-site or contractor)

Date 5-6-97