WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 71301
Permit No.
Basin 9213

NOTICE OF INTENT NO. 32567

1. OWNER MICHAEL & MELODY ARNOLD
MAILING ADDRESS P.O. Box 60912
Reno, Nevada 89506

ADDRESS AT WELL LOCATION Hungry Valley Road
Reno, Nevada 89506

2. LOCATION NE ¼ NE ¼ Sec. 24 T. 21N N/S R. 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 080-710--C9 (Parcel No.) Hungry Valley East of Lemmon Valley (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Soft brown sandy clay		2	7	5
Brown sandy clay		7	60	53
Soft zone, decomposed granite		60	68	8
Brown sandy clay		68	72	4
Granite boulder, hard		72	79	5
Brown clay		79	111	32
White sandy clay		111	168	57
Weathered granite, rusty		168	171	3
Gray granite		171	223	52
Fracture granite	X	223	227	4
Gray granite		227	243	16
Fracture granite	X	243	261	18
Gray hard granite		261	263	2

Date started 1-21-98, 19
Date completed 1-22-98, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
35		

8. WELL CONSTRUCTION
Depth Drilled 263 Feet Depth Cased 263 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches	0 Feet	50 Feet
8 5/8 Inches	50 Feet	263 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	263

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 218 feet to 258 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 263 feet

9. WATER LEVEL
Static water level 37 feet below land surface
Artesian flow G.P.M. 35 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370
RENO, NEVADA 89510 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 0022549

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed [signature] (By driller performing actual drilling on site or contractor)

Date January 24, 1998

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627