WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 73504
Permit No. 137B
Basin

NOTICE OF INTENT NO. 37961

1. OWNER ROUND MOUNTAIN GOLD CORP
MAILING ADDRESS PO BOX 480
ROUND MTN NEVADA 89045

ADDRESS AT WELL LOCATION
MINESITE IN BOTTOM OF PIT.

2. LOCATION NW ¼ NE ¼ Sec. 30 T 10 N/S R 44 E NYE County
PERMIT NO. M10-1172 (Issued by Water Resources) | Parcel No. | MINE WELL # MW 98-2 (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
POORLY WELDED RHYOLITE		0	55	55
TUFF				
DENSLEY WELDED RHYOLITE	X	55	550	495
TUFF WITH PALEOZOIC				
METASEDIMENTARY LITHICS				
FELSIC DIKE APHANITIC		550	555	5
QUARTZITE	X	555	625	70
ARGILITE		625	655	30
QUARTZITE & PHYLLITE MIXED	X	655	660	5
PHYLLITE		660	775	115
ARGILITE		775	790	15
FELSIC DIKE (RHYOLITE)		790	800	10
APHANITIC				

Date started 9-7, 19 98
Date completed 9-15, 19 98

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
WHILE DRILLING ON AIR THIS WELL MAINTAINED		
OVER 150 GPM — PSI DRILLING AT BOTTOM WAS		
180 PSI		

8. WELL CONSTRUCTION
Depth Drilled 800 Feet Depth Cased 800 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8 Inches		0 Feet	50 Feet
5 7/8 Inches		50 Feet	800 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.9	.188	+2	50
2.375	3.653	.154	+2	800

Perforations:
Type perforation MILLED
Size perforation 3 X 1/8
From EVERY OTHER feet to JOINT FROM 80 feet
From TO 800'-CAP feet to ON BOTTOM feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout X ENVIRO PLUG

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 34 feet below land surface
Artesian flow NO G.P.M. P.S.I.
Water temperature 125 °F Quality POOR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WOYTEK DRILLING CO. INC. (Contractor)
Address 2220 STOWE DRIVE (Contractor)
RENO NEVADA 89511
Nevada contractor's license number issued by the State Contractor's Board 024521A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1442
Signed Thomas M Harris (By driller performing actual drilling on site or contractor)
Date 9-17-98

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627