



HOLE ABANDONMENT REPORT

HOLE NUMBER:

OB-5

COORDINATES:

COORDINATES

north east

LOCATION: 1/4 Section

Township:

Range:

SW 1/4 NE 1/4 2 42N 53E

DATE DRILLED:

CONTRACTOR/RIG #:

HOLE DEPTH:

Rimrock 3477 300' feet

STATIC WATER LEVEL:

FLOWING WELL

(check box)

81.3 feet

AQUIFERS ENCOUNTERED:

AQUIFERS ENCOUNTERED:

NONE

(check box):

feet feet

DATE PLUGGED

PLUGGED BY
(company & rig)

SURFACE SEAL

CEMENT?

CONCRETE?

8-1-98 Summit Drilling Fluids 20 feet NEAT

Recommended Amt.

Percent

Material Used
(check box)

Amount Used

Cost/Unit

Cost

Coarse bentonite

Concrete/cement

Bentonite slurry

weight:

viscosity:

Top 20'

Nevada state regulations require:

- All holes must be plugged.
- Surface seal of neat concrete must extend to a minimum depth of 10 feet.
- IMC policy forbids backfilling holes with cuttings.
- If plugged with bentonite slurry, slurry must weigh at least 9 pounds per gallon and have a viscosity of at least 50 seconds. Barite should be used to increase the weight. More bentonite or mixing longer will increase viscosity. Soda ash added to the water first will expedite viscosity yield.
- If plugged with chipped, coarse bentonite, introduction below the water level may not exceed 50 pounds per two minutes.

REMARKS (i.e., hole left open for survey, geologic reasons):

Ran trimy to 280' - mud 13 plus 6 solids down trimy to Displace H2O
cement top 20'

Signature:

Ward Weaver

(certifies statements to be true)

3/5
2 1/2 Gels. - 50 LB. Bags
2 1/2 Barite - 100 LB. Bags

mixed 13 plus 6 solids down trimy
1 1/2 Bags 94 LB. cement

TOTAL COST
COST/FT