WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 73945
Permit No.
Basin 212

NOTICE OF INTENT NO. 18646

1. OWNER Tosco Marketing Company
MAILING ADDRESS 320 N. Pivot Drive, Tempe, Arizona 85281
ADDRESS AT WELL LOCATION 2828 East Desert Inn Road, Las Vegas, Nevada

2. LOCATION NW 1/4 NE 1/4 Sec. 16 T. 21 N/S R. 62 E. Clark County
PERMIT NO. Issued by Water Resources | Parcel No. 162-07-402-003 | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand medium to fine grained reddish brown, slightly moist, dense some gravels, no HC/HCS		0	4	
Large gravels		4	5	
Sand coarse to fine grained, reddish brown, very dense some gravels, no HC/HCS slightly moist		5	7	
Sandy clay, cohesive, slightly moist, med. dense, no HC/HCS		7	10	
Clayey sand, coarse to fine grained, pale green, very dense, no HC/HCS slightly moist		10	15	
Clayey sand, fine to medium grained reddish brown, very dense no HC/HCS, moist		15	25	

Date started 1-22, 1999
Date completed 1-25, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 25 Feet Depth Cased 10 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
6	0	25

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2			0	10

Perforations:
Type perforation SCH 40 PVC
Size perforation .020
From 10 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 9
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 9 feet to 25 feet

9. WATER LEVEL
Static water level 17 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, LLC (Contractor)
Address 301 W. Deer Valley Road #7, Phoenix, Arizona 85027 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller N0090
Signed (By driller performing actual drilling on site or contractor)
Date 2/24/99

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627