WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 73947
Permit No.
Basin 212

NOTICE OF INTENT NO. 18616

1. OWNER Tosco Marketing Company
MAILING ADDRESS 1500 N. Priest Drive
Tempe, Arizona 85284
ADDRESS AT WELL LOCATION 3498 East Desert Inn Road
Las Vegas, Nevada

2. LOCATION NW ¼ NE ¼ Sec. 16 T. 21 N/S R. 62 E/W Clark County
PERMIT NO. (Issued by Water Resources) 161-07-42-003 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other ASA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt, fine to very fine sand, loose, dry, no H2O/HCS		0	5	
Fine to very fine sand, medium dense to very dense, dry, few gravel, orangish brn, no H2O/HCS		5	7	
gravel		7	9	
Sandy clay, dry orangish brn, no H2O/HCS		9	10	
Very fine sand, gravel dense to very dense dry, grey, no H2O		10	15	
Clayey sand, medium dense to very dense slightly damp, orangish brown, no HCS/slight H2O		15	17	
Wet		17	20	
Clayey sand, medium to very dense, wet orangish brown, no H2O/HCS		20	32	
Concrete				

Date started 1-25, 1999
Date completed 1-25, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 32 Feet Depth Cased 29.5 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
6	0	32

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"			0	29.5

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 29.5 feet to 32 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 29.5
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 29.5 feet to 32 feet

9. WATER LEVEL
Static water level 17 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, Inc. (Contractor)
Address 301 W. Deer Valley Rd #7 (Contractor)
Phoenix, Arizona 85027
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller U2070
Signed (By driller performing actual drilling on site or contractor)
Date 2/24/99

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627