WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 76640
Permit No.
Basin 73A

NOTICE OF INTENT NO. 40844

1. OWNER Fred Yotter
MAILING ADDRESS 1220-457 Tasman Drive Sunnyvale, CA 94089

ADDRESS AT WELL LOCATION 11230 Park Valley drive, Lovelock Lot 225 BLK H

2. LOCATION NW 1/4 SE 1/4 Sec. 27 T 30 N/S R 33 E Pershing County
PERMIT NO. (Issued by Water Resources) Parcel No. 10-543-24 Subdivision Name Humboldt River Ranch Phase F

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Cobbles		0	190	
Fractured rock		190	240	50
Cobbles		240	380	140
Gravel & cobbles		380	443	63

Date started 4-26, 1999
Date completed 4-30, 1999

7. WELL TEST DATA

TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20		4

8. WELL CONSTRUCTION
Depth Drilled 445 Feet Depth Cased 443 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11	Inches	0	Feet	50	Feet
8-3/4	Inches	50	Feet	443	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8		.188	+2	443

Perforations:
Type perforation Single row mill slot
Size perforation 1/8 x 3
From 383 feet to 443 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 320 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1154-T1

Signed Jerry A. Tompk
By driller performing actual drilling on-site or contractor

Date 5/5/99