WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY
LK42
PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 76646
Permit No.
Basin 51

NOTICE OF INTENT NO. 30127

1. OWNER Newmont Gold Co.
MAILING ADDRESS P.O. Box 669 Carlin NV. 89822
ADDRESS AT WELL LOCATION At Gold Quarry Pit 8 Miles North of Carlin NV.

2. LOCATION NW ¼ SW ¼ Sec. 2 T. 33 N/S R. 51 E. Eureka County
PERMIT NO. 56834 Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill		0	85'	85
Alluvium Clay & Gravel		85'	675'	590
Bed Rock		675'	685'	10'
¾" Hole Plug		0	105'	105'
Pea Gravel		105'	680'	575'
Neat Cement		680'	685'	5
16" Casing Had ¾" Hole Plug From 103 to 10' Cement From 10' to Surface				
Plugged by NOI #61122				
40.773657°N				
116.213959°W NAD 27 (T)				
* See plugging log # 109097				

Date started 4-12, 19 99
Date completed 4-27, 19 99

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
200'		5	5 min.
300'		30	5 min.
400'		60	5 min.
500'		70	5 min.
600'		70	5 min.
685'		70	5 min.

8. WELL CONSTRUCTION
Depth Drilled 685' Feet Depth Cased 685' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
16"	Inches	0	Feet	103'	Feet
12"	Inches	103'	Feet	685'	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12 5/8"		¼ wall	0	103'
8 5/8"		¼ wall Blank	+2	178'
8 5/8"		¼ wall Screen	178	680'
8 5/8"		¼ wall Bank	680'	685'

Perforations:
Type perforation Horz. Lewvers
Size perforation ⅛" Horz. Lewvers
From 178' feet to 680' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 10'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 90' feet to 685' feet

9. WATER LEVEL
Static water level 203' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Clean

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co. Contractor
Address 605 union Pacific way Contractor
P.O. Box 2748 Elko NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1786
Signed Craig Dines By driller performing actual drilling on site or contractor
Date 4-27-99

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627