

253

WHITE-DIVISION OF WATER RESOURCES
CANARY-CLIENT'S COPY
PINK-WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY

Log No. 79049

Permit No. 61

Basin 61

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 43226
Barrick Goldstrike

1. OWNER Barrick Goldstrike ADDRESS AT WELL LOCATION Barrick Goldstrike Minesite, North of Carlin, NV

MAILING ADDRESS P.O. Box 29
Elko, NV 89803

2. LOCATION SE $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 19 T. 36 N S R. 50 E Eureka County

PERMIT NO. N/A Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED New Well Replace Recondition Deepen Abandon Other

4. PROPOSED USE Domestic Municipal/Industrial Irrigation Monitor Test Stock

5. WELL TYPE Cable Rotary RVC Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Black, Grey & White Rock		0	35	35
Grey & Black Rock		35	120	85
Black Rock		120	130	10
Grey Clay & Rock		130	150	20
Grey & White Rock		150	185	35
Grey Rock & Clay		185	200	15
Grey, White & Black Rock		200	300	100
Grey & White Rock		300	380	80
Grey & Black Rock		380	405	25
Black & White Rock		405	420	15
Black, White & Grey Rock		420	445	25
Grey & White Rock		445	465	20
Grey Rock		465	480	15
Grey, Black & White Rock		480	537	57

Construction Detail:

Cement	0	50
3/8 Hole Plug	50	500
3/8 Gravel	500	537

8. WELL CONSTRUCTION

Depth Drilled 537 Feet Depth Cased 510 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
14 3/4 Inches	0	40
8 Inches	40	537

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.750	34.24	0.250	+1	40
2.375	3.65	0.154	+2	530

Perforations: slotted

Type perforation 0.125"

Size perforation 0.125"

From 510 feet to 530 feet

Surface Seal: Yes No Seal Type: Neat Cement Cement Grout Concrete Grout

Depth of Seal 50'

Placement Method: Pumped Poured

Gravel Packed: Yes No

From 500 feet to 537 feet

Date started 2 September 1999

Date completed 10 September 1999

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WATER LEVEL

Static water level 270 feet below land surface

Artesian flow N/A G.P.M. P.S.I.

Water temperature Cool F Quality Fair

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor

Address P.O. Box 5279 Contractor

Elko, NV 89802

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources / the on-site driller 2085

Signed [Signature] By driller performing actual drilling on site or contractor

Date 9/13/99