

STATE OF NEVADA
 DIVISION OF WATER RESOURCES

OFFICE USE ONLY

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. 79115
 Permit No. _____
 Basin 61

NOTICE OF INTENT NO. 43228

1. OWNER BARRICK GOLDSTRIKE MINES ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINESITE, NORTH OF CARLIN, NV.
 MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

2. LOCATION NE 1/4 NW 1/4 Sec. 30 T. 36 N/S R. 50 E EUREKA County
 PERMIT NO. N/A Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
BLACK & GREY ROCK		0	140	140
BLACK, WHITE, & GREY ROCK		140		
GREY ROCK & CLAY		190	200	10
GREY & BLACK ROCK		200	335	135
GREY ROCK		335	355	20
GREY CLAY		355	360	5
GREY ROCK		360	375	15
GREY & BLACK ROCK		375	440	65
BLACK, GREY & WHITE ROCK		440		
GREY ROCK			470	30
GREY & WHITE ROCK		470	480	10
		480	500	20

8. WELL CONSTRUCTION
 Depth Drilled 500 Feet Depth Cased 430 Feet
 HOLE DIAMETER (BIT SIZE)
 From 14.75 Inches 0 Feet 38 Feet
 To 8.25 Inches 38 Feet 500 Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.750	40.48	.365	0	38
1:2.375	5.02	.218	+1	450
2:2.375	5.02	.218	+1	360

Perforations:
 Type perforation SLOTTED
 Size perforation 0.125"
 From 1: 430 feet to 450 feet
 From 2: 320 feet to 360 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 50' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No SEE DETAIL
 From _____ feet to _____ feet

9. WATER LEVEL
 Static water level 1:298 2:326 feet below land surface
 Artesian flow N/A G.P.M. _____ P.S.I. _____
 Water temperature 78 °F Quality FAIR

CONSTRUCTION DETAIL:
 CEMENT 0 50
 HOLE PLUG 50 309
 GRAVEL 309 370
 HOLE PLUG 370 438
 GRAVEL 438 473
 HOLE PLUG 473 500

Date started SEPTEMBER 13 19 99
 Date completed SEPTEMBER 19 19 99

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name LANG EXPLORATORY DRILLING Contractor
 Address P.O. BOX 29 Contractor
ELKO, NV 89802
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources on-site driller 2085
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date SEPTEMBER 21, 1999

B.S.L