WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79179
Permit No.
Basin 72

NOTICE OF INTENT NO. 41837

1. OWNER FLORIDA CANYON MINING, INC.
MAILING ADDRESS P.O. BOX 330
IMLAY, NV 89418

ADDRESS AT WELL LOCATION 6 MILES SW OF IMLAY, NV

2. LOCATION SE 1/4 SW 1/4 Sec. 34 T 32N N/S R 33E E PERSHING County
PERMIT NO. MO-0-737 (Issued by Water Resources) | WELL MW9 (Parcel No.) | TRACT OF LAND (Subdivision Name)

3. **WORK PERFORMED**
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. **PROPOSED USE**
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. **WELL TYPE**
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. **LITHOLOGIC LOG**

Material	Water Strata	From	To	Thickness
Remove pump from well - pulled steel monument - drilled out pvc casing to 170' - pumped abandonite from bottom up - placed 3/4" bentonite chips above abandonite - pumped cement seal top 20 feet				
Material used:				
16 50# bags of abandonite mixed w/ 640 gallons of water				
11 50# bags of 3/4 bentonite chips				
2 50# bags of casing seal				
5 94# bags of portland cement mexed w/ 35 gallons of water				

RECEIVED 99 SEP 20 PM 12:01 STATE ENGINEERS OFFICE

Date started 8/4/99, 19__
Date completed 8/5/99, 19__

7. **WELL TEST DATA**
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. **WELL CONSTRUCTION**
Depth Drilled 170 Feet Depth Cased Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8.5	Inches	0	Feet	170	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
n/a				

Perforations:
Type perforation n/a
Size perforation n/a
From n/a feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal 20
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From n/a feet to feet

9. **WATER LEVEL**
Static water level 140 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name HACKWORTH DRILLING, INC (Contractor)
Address P.O.BOX 850 (Contractor)
ELKO,NV 89803
Nevada contractor's license number issued by the State Contractor's Board 020582
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1654
Signed (By driller performing actual drilling on-site or contractor)
Date 8/5/99

USE ADDITIONAL SHEETS IF NECESSARY