WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79191
Permit No.
Basin 87

NOTICE OF INTENT NO. 44101

1. OWNER Washoe Keystone Partnership
MAILING ADDRESS 1155 W. 4th Street #225 Reno, NV 89503
ADDRESS AT WELL LOCATION MW-3 1001 W. 4th Street; Reno, NV

2. LOCATION NE ¼ SE ¼ Sec. 10 T. 19 N/S R. 19 E. Washoe County
PERMIT NO. N/A (Issued by Water Resources) 06-222-23 (Parcel No.) N/A (Subdivision Name)

3. MW-3 WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt (A/C)		0.0	0.5	0.5
DK BR SILTY SAND (SM) w/ GRAVEL DENSE MOIST.		0.5	3.0	2.5
COBBLES VERY DENSE		3.0	4.0	1.0
BR CLAYEY SAND (SC) w/ GRAVEL DENSE MOIST.		4.0	9.0	5.0
GREY BLACK CLAY (CH) VERY STIFF MOIST.		9.0	16.0	7.0
BLK CLAYEY SAND (SC) w/ GRAVEL DENSE MOIST.		16.0	23.0	7.0
BLK SAND (SP) DENSE VERY MOIST.		23.0	25.0	2.0
GREY BLACK GRAVELS & SM COBBLES (G/C W) VERY DENSE		25.0	31.0	6.0
WATER LEVEL	26.0			

Date started Feb 11, 2000, ~~19~~
Date completed Feb 14, 2000, ~~19~~

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 31.0 Feet Depth Cased 31.0 Feet

HOLE DIAMETER (BIT SIZE)
From To
1¾ Inches 0.0 Feet 31.0 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.70	0.308	21.0	0.0

Perforations:
Type perforation Slotted
Size perforation 0.020
From 31.0 feet to 21.0 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 16.0' - 0.0 ft
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Bentonite (18.0 - 16.0)
~~Gravel~~ Sand #12 Packed: ☒ Yes ☐ No
From 31.0 feet to 18.0 feet

9. WATER LEVEL
Static water level 26.0 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Dale Lehman (Contractor)
Address Pezonella Assoc. (Contractor)
520 Edison Way; Reno, NV 89502
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1976
Signed Dale Lehman (By driller performing actual drilling on site or contractor)
Date 2/16/00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627