WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79211
Permit No. 87
Basin

NOTICE OF INTENT NO. 44101

1. OWNER Washoe Keystone Partnership
MAILING ADDRESS 1155 W. 4th Street # 225 Reno, NV 89503
ADDRESS AT WELL LOCATION MW-2 1001 W. 4th Street, Reno, NV

2. LOCATION NE ¼ SE ¼ Sec. 10 T. 19 N/S R. 19 E. Washoe County
PERMIT NO. N/A (Issued by Water Resources) 06-222-23 (Parcel No.) N/A (Subdivision Name)

3. MW-2 WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CONCRETE SLAB		0.0	0.5	0.5
COBBLES & LG. GRAVELS		0.5	5.0	4.5
IN CLAYEY SAND MATRIX				
VERY DENSE SLIGHTLY MOIST				
GREY BLACK CLAY (CH)		5.0	25.0	20.0
VERY STIFF MOIST				
BR SILTY GRAVELS (GM)		25.0	30.5	5.5
W/ SAND + COBBLES				
VERY DENSE MOIST.				
WATER LEVEL	26.0			

00 FEB 18 PM 12:12
STATE ENGINEER'S OFFICE

Date started Feb 15, 2000, 19__
Date completed Feb 15, 2000, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30.5 Feet Depth Cased 30.5 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
7 3/4 Inches	0.0 Feet	30.5 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.70	0.308	20.5	0.0

Perforations:
Type perforation slotted
Size perforation 0.020
From 30.5 feet to 20.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 14.0 - 0.0 ft
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
bentonite (16.0 - 14.0)
sand #12
~~Gravel~~ Packed: ☒ Yes ☐ No
From 30.5 feet to 16.0 feet

9. WATER LEVEL
Static water level 26.0 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Dale Lehman (Contractor)
Address Pezonella Assoc. (Contractor)
520 Edison Way, Reno, NV 89502
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1976
Signed Dale Lehman (By driller performing actual drilling on site or contractor)
Date 2/16/00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627