WHITE--DIVISION OF WATER RESOURCES
CANARY--CLIENT'S COPY
PINK--WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79508
Permit No.
Basin

NOTICE OF INTENT NO.

1. OWNER Bureau of Land Management
MAILING ADDRESS 50 Bastian Rd
Battle Mnt, Nv 89820
ADDRESS AT WELL LOCATION Stewart Mill Site

2. LOCATION SE ¼ NW ¼ Sec. 23 T. 19 N/S R. 43 E. Lander County
PERMIT NO. Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☑ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other pulling unit

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
3-6-00				
Mobilize To Location				
& pull Pump				
3-7-00				
Resize Hydralic Perferating Tool				
3-8-00				
Perferate 10" hole				
0-50 220-340				
with hydralic perferating tool				
3-9-00	Abentonite			
mix 1 2 Sac mix 8.5 lbs per gallon				
1 2.5 Sac mix 8.8 lbs per gallon				
17 3 Sac mix 9.0+ lbs per gallon				
Raised Static water Level To				
108 FT				
monitor Static For 30 minutes Dropped To				
~~Drop~~ 112'				
Drop 3/4" hole plug 60 Sacs Raise				
Bottom To 52"				
mix	Cement			
2 10 Sac mixs 15.1+ lbs P/G				
2 5 Sac mixs 14.8+ lbs P/G				
Filled hole To Surface				

Date started March 6 2000
Date completed March 9 2000

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 400 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.250			10	396
14.000			+2	?

Perforations:
Type perforation Apparently 300 - 400
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 292 feet below land surface
Artesian flow NO G.P.M. P.S.I.
Water temperature ? °F Quality ?

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Fred Anderson Drilling, Inc (Contractor)
Address 10760 Grass Valley Road (Contractor)
Winnemucca, Nv 89445
Nevada contractor's license number issued by the State Contractor's Board 021467
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 01375
Signed (By driller performing actual drilling on site or contractor)
Date March 10-00

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627