

OFFICE USE ONLY
 Log No. 79562
 Permit No. 93
 Basin 93

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 43858

1. OWNER BARBARA BLOOM ADDRESS AT WELL LOCATION Ruby Hill Road
 MAILING ADDRESS 338 Rider Road Corralitos, CA 95076 Reno, NV 89506
 2. LOCATION SE 1/4 NEW 1/4 Sec. 35 T 23N N/S R. 19 E. Washoe County
 PERMIT NO. 079-530-08 Antelope Valley
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Decomposed granite sands		2	6	4
Decomposed granite		6	18	12
Weathered soft granite				
with clay streaks		18	41	23
Soft zone		41	44	3
Weathered soft granite				
with clay streaks		44	88	44
Weathered granite		88	160	72
Gray hard granite		160	171	11
Rusty weathered granite		171	174	3
Gray granite		174	305	131
Weathered granite softer				
some clay streaks		305	401	96
Gray granite		401	527	126
Soft zone (NO WATER)		527	529	2
Gray granite		529	595	66
Soft zone	X	595	607	12
Weathered granite		607	630	23
Fracture	X	630	640	10
Weathered granite		640	650	10

8. WELL CONSTRUCTION
 Depth Drilled 650 Feet Depth Cased 650 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
10 Inches 0 Feet 50 Feet
8 5/8 Inches 50 Feet 650 Feet
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	650

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3 x 5 around
 From 585 feet to 645 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Depth of Seal 50 feet Cement Grout
 Placement Method: Pumped Concrete Grout
 Poured
 Gravel Packed: Yes No
 From 50 feet to 650 feet

9. WATER LEVEL
 Static water level 505 feet below land surface
 Artesian flow _____ G.P.M. 25 P.S.I.
 Water temperature cold °F Quality clear

Date started March 9, 2000 19XX
 Date completed March 13, 2000 19XX

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO., NEVADA 89510
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board
 Nevada driller's license number 923
 issued by the Division of Water Resources, the on-site driller
 Signed [Signature]
 by driller performing actual drilling on site or contractor
 Date March 16, 2000