277

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79972
Permit No.
Basin 92B 92A

NOTICE OF INTENT NO. 42702

1. OWNER Washoe County Dept. Water Res.
MAILING ADDRESS 4930 Energy Way
Reno NV 89502

ADDRESS AT WELL LOCATION Stead

2. LOCATION SE ¼ NE ¼ Sec. 1 T. 20 N/S R. 18 E. Stead Washoe County

PERMIT NO. 00651 (Issued by Water Resources) | 09001004 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy gravel		0		10
Sandy gravel		10		20
Sandy Clay w-Silt	2"	20		30
Sandy Clay w-gravel		30		40
Sandy Clay w-gravel		40		50
Sandy Clay w-gravel		50		60
Sandy Clay w-gravel		60		70
Silt w-Clay		70		80
Clay w-Silt		80		90
Clay w-Silt		90		100
Clay w-Silt		100		110
Silt w-Clay		110		120
Clay		120		130
Clay		130		140
Silt w-Clay & Sand		140		150
Silt w-Clay		150		160
Clay w-Sand & Silt		160		170
Clay w-Sand & Silt		170		180
Sand		180		190
Sand		195		195

Date started 12-7-99, 19
Date completed 12-10-99, 19

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 195 Feet Depth Cased 195 Feet

HOLE DIAMETER (BIT SIZE)
9" Inches From 0 Feet To 195 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		SC 40	0	195

Perforations:
Type perforation Factor Cut
Size perforation 040
From 165 feet to 195 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 195
Placement Method: ☒ Pumped ☐ Poured

Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 0 feet to 165 feet

9. WATER LEVEL
Static water level 180 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name West Hazmat (Contractor)
Address 3233 Kitzgarld (Contractor)
Rancho Cordova Ca 95742
Nevada contractor's license number issued by the State Contractor's Board 31386
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M2079
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 1-27-00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

log # 79972

I

75 slit w/clay
70 slit w/clay
75 clay w/slit & gravel
80 clay w/slit & sand
85 clay w/slit & sand
90 clay w/ slit & sand
95 clay w/sand
100 clay w/sand
105 slit w/clay & sand
110 slit w/clay
115 clay
120 clay
125 clay
130 clay
135 clay
140 slit w/ ~~sand~~ clay & sand
145 clay w/ slit
150 slit clay
155 clay w/slit
160 clay w/sand & slit
165 no sample
170 NO sample
175 clay w/slit & sand

180 ~~clay w/slit~~ & sand
185 ~~clay~~ slit & sand
190 sand & slit
195 sand & slit
200

10' over

@ 20'