WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80298
Permit No.
Basin 212

NOTICE OF INTENT NO. 21356

1. OWNER Bob Denino 7-11 Inc.
MAILING ADDRESS 10220 S.W. Greenburg Rd Portland OR 97223
ADDRESS AT WELL LOCATION 7-11 Inc. 600 N Las Vegas Blvd NV.

2. LOCATION SE ¼ SE ¼ Sec. 27 T 20 N/S R 61 E 7-11 Inc. Clark County
PERMIT NO. (Issued by Water Resources) Parcel No. 139-27-805-004 Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Hand

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
MW-12				

Date started 4-13-00, 19
Date completed 4-13-00, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 5' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10" Inches	0 Feet	30' Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"			0	5

Perforations:
Type perforation SCH 40 PVC
Size perforation .020
From 5' feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name THF Drilling Inc. (Contractor)
Address 9431 Resanda Ave. (Contractor)
Fontana CA. 92335
Nevada contractor's license number issued by the State Contractor's Board 045849
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1747-77
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

SECOR INTERNATIONAL INCORPORATED
LOG OF EXPLORATORY BORING

80298

Project No. 020.90132	Tot. Depth (ft.): 30	Ground Elev. (ft.): N/A	BORING No. MW-12
Date Drilled: 04/13/00	Drive wt. (lbs): 140	Groundwater Elev (ft.):	Sheet 1 of 1
Logged By: B. Loffman	Drop Dist. (in.): 30	▽ 17	
	Casing Elev. (ft): N/A	▼ N/A	

Drilling Co: THF Drilling
Drilling Method: HSA
Boring Dia. (in.): 10

Remarks: Boring designated WA prior to completion as MW-12

7-11 #27607

600 N LAS VEGAS BLVD

Well Construction	Depth (ft.)	Sample Type	Blows per 6 in.	Graphic Log	Description	Volatile Reading (ppmv)	Sample Analysis	Sample Designation
12" Traffic Rated well box	0				ASPHALT: Asphalt surface 2".			
4" 40 sch Blank PVC Casing					FILL: SILTY GRAVEL: Asphalt underlain by silty gravel fill road base, very pale orange, slightly moist, no hydrocarbon odor (HCO), no hydrocarbon staining (HCS).			
	-5				NATIVE: CALICHE: Highly cemented, pale yellowish gray (5Y 8/1), dry, no HCO/HCS.			
Concrete/ Grout					GRAVEL: (GP) Gravel beds within caliche.			
	-10				CALICHE: Highly cemented.			
Bentonite Chips		C	26-40-29		SANDY CLAY: (CL) Sandy clay w/ some subrounded gravels, medium light gray (N6), moist, HCO/HCS.	98	70 mg/kg	WA-12.5
	-15	C ▽	27-32-16		SAND: (SM) Medium-coarse sand, some silt, light gray (N7), well graded, wet, heavy HCO/HCS.	158	<10 mg/kg	WA-17
No. 3 Sand Pack	-20				SANDY CLAY: (CL) Some gravels, very light gray, wet.			
4" 40 sch 0.02 Slotted Screen	-25							
End Cap	-30							