WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80366
Permit No.
Basin 212

NOTICE OF INTENT NO. 21360

1. OWNER Broadbent & Associates
MAILING ADDRESS 8 West Pacific Avenue
Henderson, NV 89015

ADDRESS AT WELL LOCATION ARCO Station 5328, 1500
W Bonanza (NWC Bonanza & Martin Luther King), Las Vegas, NV

2. LOCATION NE 1/4 SW 1/4 Sec. 28 T 20S N/S R 61E E Clark County
PERMIT NO. (Issued by Water Resources) 139-28-304-007 (Parcel No.) MW-9 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphalt		0	0.5	.5
Type II Backfill		0.5	3.0	2.5
Silty fine to medium		3.0		
SAND, trace Clay (SM)			5.0	2
Silty CLAY, some fine		5.0		
to medium Sand, little				
coarse Sand, trace				
fine Gravel (ML)			8.5	3.5
Caliche		8.5	17.0	8.5
Silty CLAY, little		17.0		
fine to medium Sand,				
trace coarse Sand (ML)			25.0	8

Date started 6/7/2000, 19__
Date completed 6/7/2000, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 25 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 inches	Inches	0 Feet	25 Feet
	Inches	Feet	Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	1.9	0.237	0	25

Perforations:
Type perforation Factory slot PVC
Size perforation 0.020
From 10 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-5', 5'-7'bentonite
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 7 feet to 25 feet

9. WATER LEVEL
Static water level 17 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Tom High c/o Converse Consultants (Contractor)
Address 731 Pilot Road, Suite H (Contractor)
Las Vegas, NV 89119
Nevada contractor's license number issued by the State Contractor's Board 48947
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1869
Signed (By the person performing actual drilling on-site for contractor)
Date 6/9/2000

USE ADDITIONAL SHEETS IF NECESSARY