

WHITE-DIVISION OF WATER RESOURCES  
CANARY-CLIENT'S COPY  
PINK-WELL DRILLER'S COPY

STATE OF NEVADA

DIVISION OF WATER RESOURCES

OFFICE USE ONLY

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. 81336  
Permit No. 01  
Basin

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

NOTICE OF INTENT NO. 43236

1. OWNER BARRICK GOLDSTRIKE MINES ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE  
MAILING ADDRESS P.O. BOX 29 MINESITE, NORTH OF CARLIN, NV.  
ELKO, NV 89803

2. LOCATION SW 1/4 NE 1/4 Sec. 19 T. 36 N S R. 50 E EUREKA County  
PERMIT NO. Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
BROWN SAND WITH BLACK & GREY ROCK		0	195	195
COMPACTED BROWN & GREY SAND	208'	195	300	105
REDDISH BROWN SAND, BLACK & GREEN ROCK	TRACE	300	305	5
WEATHERED GREY ROCK		305	310	5
TAN COMPACTED SAND, GREY ROCK		310	315	5
BLACK, BROWN, GREEN GRAVEL		315	360	45
WHITE SAND CLAY		360	365	5
BLACK, GREY, BROWN ROCK	5GPM	365	385	20
WHITE CLAY, BLACK ROCK		385	390	5
BLACK, GREY ROCK		390	410	20
WHITE CLAY, BLACK ROCK		410	415	5
BLACK, GREY, BROWN ROCK & GRAVEL	5 GPM	415	450	35
CONSTRUCTION DETAIL:				
CEMENT		0	51	51
HOLE PLUG		51	273	222
GRAVEL PACK		273	305	32
HOLE PLUG		305	334	29
GRAVEL PACK		334	345	11
TRANSDUCER			340	
HOLE PLUG		345	375	30
GRAVEL PACK		375	426	51
HOLE PLUG		426	450	24

8. WELL CONSTRUCTION  
Depth Drilled 450 Feet Depth Cased 420 Feet  
HOLE DIAMETER (BIT SIZE)  
From To  
1.4.75 Inches 0 Feet 24 Feet  
7.875 Inches 24 Feet 450 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.75	28.04	0.250	0	24
1:2.375	5.02	0.218	0	420
2:2.375	5.02	0.218	0	300

Perforations:  
Type perforation SLOT  
Size perforation 0.125"  
From 1: 380 feet to 420 feet  
From 2: 280 feet to 300 feet

Surface Seal:  Yes  No Seal Type:  
Depth of Seal 5.1'  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
Gravel Packed:  Yes  No  
From 1: 375 feet to 305 feet to 1: 426 2: 375 feet

9. WATER LEVEL  
Static water level 1: 337 2: 273.5 feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature °F Quality

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name LANG EXPLORATORY DRILLING Contractor  
Address P.O. BOX 5279 Contractor  
ELKO, NV 89802-5279  
Nevada contractor's license number issued by the State Contractor's Board 0021976  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1888  
Signed David Dorot By driller performing actual drilling on site or contractor  
Date AUGUST 2, 2000

Date started JULY 24, 2000  
Date completed JULY 27, 2000

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

B.S.T.A.