WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 82169
Permit No.
Basin 61

NOTICE OF INTENT NO. 38323

1. OWNER Barrick Goldstrike Mines - BW-5
MAILING ADDRESS P. O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike
Minesite, North of Carlin, NV.

2. LOCATION SE 1/4 NW 1/4 Sec. 24 T 36N N/S R 49E E Eureka County
PERMIT NO. 54916T,54917T,54918T Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Abandoned per procedure discussed with DWR.				
Note: Some original construction details are not shown at right, as they were not given on the original well report. Also, some data differ from original state report; these were taken from the clients as-built.				
Abandoned by pouring hole plug mixed with abantonite to 495', placed 50' of neat cement, backfilled to 1', capped with neat cement.				
Quantities Used:				
Cement: 1 cu.ft.		0	1	1
Backfill: 620 cu.ft.		1	445	444
Cement: 70 cu.ft.		445	495	50
Hole plug: 1518 cu.ft.		495		
Abantonite: 110 cu.ft.			1570	1075

Date started 11/24/2000, 19__
Date completed 11/24/2000, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1593 Feet Depth Cased 1580 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
	Inches	0	Feet	50	Feet
22	Inches	50	Feet	1593	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
24			+1	50
16	62.58	0.3750	+2	480
16	52.27	0.3125	480	1570

Perforations:
Type perforation Louver
Size perforation 0.125" X 2.500"
From 640 feet to 1560 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 1593 feet

9. WATER LEVEL
Static water level Dry feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2143
Signed Brant Bowen (By driller performing actual drilling on-site or contractor)
Date 12/5/00

USE ADDITIONAL SHEETS IF NECESSARY