

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 21623

1. OWNER Antonio Hernandez ADDRESS AT WELL LOCATION Lander St. Amargosa Valley, Nv. 89020  
 MAILING ADDRESS HCR 69 Box 414-A Amargosa Valley, Nv. 89020  
 2. LOCATION NW 1/4 NE 1/4 Sec. 2 T. 18 N. R. 49 E Nye County  
 PERMIT NO. 19-462-20 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  Deepen  Abandon  Other  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVG  Air  Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Cemented gravel-w/ sand layers		0	50	50
brown cly.		50	55	5
Gravel		55	65	10
Red cly.		65	80	15
White cly.		80	94	14
Gravel	SE	94	102	8
snd.		102	115	13
Limestone		115	118	3
Gravel		118	127	9
Limestone		127	130	3
snd.		130	145	15
Limestone		145	162	17
Limestone w/cly. layers		162	180	18
Bottom of Hole			180	

8. WELL CONSTRUCTION  
 Depth Drilled 180 Feet Depth Cased 180 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 12 1/2 Inches To 180 Feet  
 From 0 Feet To 180 Feet  
 From 0 Feet To 180 Feet

CASING SCHEDULE


Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
0	PVC		0	200
7x8"	steel	.1808	Surface Protective Casing	

Perforations:  
 Type perforation Machined  
 Size perforation 3" x 1/8" Every 12"  
 From 105 feet to 160 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout  
 Depth of Seal 50  
 Placement Method:  Pumped  Poured  
 Gravel Packed:  Yes  No  
 From 50 feet to 180 feet

9. WATER LEVEL  
 Static water level 97 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature Cool °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Cook's Drilling Co  
 Address HCR 70 Box 543 Amargosa Valley, Nv. 89020  
 Nevada contractor's license number issued by the State Contractor's Board 5376A  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2160  
 Signed Reed Johnson  
 By driller performing actual drilling on site or contractor  
 Date 3/12/01



Date started March 6, 2001  
 Date completed March 8, 2001

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)