

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 83464  
 Permit No. 55141  
 Basin 61

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38349

1. OWNER **Barrick Goldstrike Mines** ADDRESS AT WELL LOCATION **Barrick Goldstrike minesite, north of Carlin, NV.**  
 MAILING ADDRESS **P.O. Box 29 Elko, NV 89803**

2. LOCATION NW 1/4 NE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County  
 PERMIT NO. 55141 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  Monitor  Municipal/Industrial  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Pump lodged in well while being pulled. Bottom of pump at 458', 3" column pipe extends from top of pump to surface.				
Abandoned per protocol discussed with DWR.				
Filled 3" column pipe with neat cement, via tremmie. Pumped neat cement from top of pump to surface.				
Quantities Used:				
Neat cement: 212 cu.ft.		0	450	450

8. WELL CONSTRUCTION  
 Depth Drilled 1120 Feet Depth Cased 1100 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
20.5 Inches	0 Feet	36 Feet
14.75 Inches	36 Feet	1120 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42.05	0.250	0	36
8.625	22.36	0.250	0	1100

Perforations:  
 Type perforation Louver  
 Size perforation 0.125"

From	To
117 feet	1100 feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  
 Depth of Seal 100'  Cement Grout  
 Placement Method:  Pumped  Concrete Grout  
 Poured

Gravel Packed:  Yes  No  
 From 102 feet to 1120 feet

Date started 4/26/2001 19  
 Date completed 4/27/2001 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

9. WATER LEVEL  
 Static water level 740' feet below land surface  
 Artesian flow N/A G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor  
 Address P.O. Box 5279 Contractor  
Elko, Nv 89802-5279  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1716

Signed David Daas  
 By driller performing actual drilling on-site or contractor  
 Date 5/1/01