WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 83971
Permit No. 634
Basin

NOTICE OF INTENT NO. 45059

1. OWNER MIKE & ERIN BRANCH
MAILING ADDRESS 11035 Wagon Ho Lane
Reno, Nevada 89506

ADDRESS AT WELL LOCATION 1270 ~~Lot 42~~ Goldstone
Reno, Nevada 89506

2. LOCATION NE ¼ SE ¼ Sec. 24 T 22N N/S R 18 E Washoe County
PERMIT NO. (Issued by Water Resources) 079-362-18 (Parcel No.) Red Rock Estates lot 42 (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clay		1	3	2
Brown fine sand		3	9	6
Brown sandy clay		9	36	27
Soft zone, fine brown sand		36	38	2
Brown sandy clay		38	101	63
Softbrown sand with Mica & small gravels		101	110	9
Brown sandy clay		110	161	51
Soft zone (NO WATER)		161	164	3
Brown sandy clay		164	186	22
Soft zone (app 5 GPM)	X	186	189	3
Soft brown sandy clay		189	246	57
Weathered granite with clay streaks		246	279	33
Soft weathered granite	X	279	281	2
Weathered granite with clay streaks		281	299	18
Soft zone	X	299	301	2
Weathered granite with clay streaks, soft		301	374	73
Soft weathered granite		374	381	7
Weathered granite with clay streaks		381	400	19

Date started April 30, 2001, 19
Date completed May 2, 2001, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30		

8. WELL CONSTRUCTION
Depth Drilled 400 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	400 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	400

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 4 x 5 around
From 215 feet to 235 feet
From 295 feet to 315 feet
From 375 feet to 395 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 400 feet

9. WATER LEVEL
Static water level 109 feet below land surface
Artesian flow G.P.M. 30 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed [signature] (By driller performing actual drilling on site or contractor)
Date May 7, 2001

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627