WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 84148
Permit No.
Basin 212

NOTICE OF INTENT NO. 20050

1. OWNER William & Barbara Austin
MAILING ADDRESS
ADDRESS AT WELL LOCATION 4920 N. Bruce

2. LOCATION NW ¼ SE ¼ Sec. 35 T. 19 X N/S R. 61 E. Clark County
PERMIT NO. (Issued by Water Resources) Parcel No. 124-35-701-003 Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Caliche stringers | w/ | 0 | 120 | 120 |
| White clay | | | | |
| White clay, caliche | | | | |
| stringers of gravel | | 120 | 180 | 60 |
| Brown clay & gravel | | 180 | 220 | 40 |
| White clay, stringers | | 220 | 250 | 30 |
| of gravel | | | | |

Date started 8/10/01, 19
Date completed 8/17/01, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 12 1/4 Inches | 1 Feet | 250 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 8 5/8 | | .188 | +1 | 250 |
| | | | | |
| | | | | |

Perforations:
Type perforation mill slot
Size perforation 1/8
From 150 feet to 250 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 52
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 52 feet to 250 feet

9. WATER LEVEL
Static water level 120 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Thompson Drilling Co., Inc. (Contractor)
Address 7227 Hauck Street (Contractor)
Las Vegas, NV 89118
Nevada contractor's license number issued by the State Contractor's Board 4286A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2074
Signed Richard K. Thompson (By driller performing actual drilling on site or contractor)
Date 8/21/01

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627