WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 85359
Permit No.
Basin 102

NOTICE OF INTE[redacted]74419

1. OWNER Wade Robenson
MAILING ADDRESS
ADDRESS AT WELL LOCATION 3365 W. Spruce Silver Springs, Nevada

2. LOCATION NW ¼ NE ¼ Sec. 34 T. 18 N/S R. 24 E. Lyon County
PERMIT NO. (Issued by Water Resources) 018-380-02 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Soil / Sand		0	4	
Gravel Boulders		4	70	
Gravel, Clay Boulders		70	102	
Tan Clay		102	115	
Gravel Sand		115	123	
Tan Clay		123	152	
Gravel Sand		152	154	
Tan Clay		154	191	
Tan Sand		191	198	
Black clay with Gravel seams		198	260	

Date started 12-11 2001
Date completed 12-12 2001

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Produced about 40	GPM	

8. WELL CONSTRUCTION
Depth Drilled 260 Feet Depth Cased 260 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8 Inches		0 Feet	Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.00	.3116	+1	20
6 5/8	3.00	SCH 40		

Perforations:
Type perforation Gill / Saw
Size perforation 1/4 x 5 1/2 Long Slots
From 180 feet to 260 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-50
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 50 feet to 260 feet

9. WATER LEVEL
Static water level 123 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Floyd Phillips Inc (Contractor)
Address PO Box 574 (Contractor)
Silver Springs NV 89429
Nevada contractor's license number issued by the State Contractor's Board 0031811
Nevada driller's license number issued by the Division of Water Resources, the on site driller 1877
Signed (By driller performing actual drilling on site or contractor)
Date 12-12-01

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627